

Project:

# Thin-Line LED Pendant Spec Sheet

SKU: 2816.03-6-27 Learn more at:

https://sonnemanlight.com/thin-line-led-pendant

Description:

A system of minimally scaled LED linear pendants, uplight/downlight wall bars, and indirect light wall bars, Thin-Line is offered in a variety of lengths, finishes, and lighting configurations. Thin-Line pendants are available in single- and double-sided configurations; the single-sided configurations can be installed as a downlight or up-light, providing direct or indirect illumination. Our Optional Mini Box Canopy is also available for the Thin-Line LED

Type #:





### **Dimensions**

Height: 72" Width: Length: 0.75" 4.5" Canopy/Backplate/Base:

6' One-Sided Size:

**Electrical Specs** 

Bulb(s) Included?: Yes Integral LED Bulb 1 Type: **Bulb Quantity:** Input Voltage: 120VAC Wattage: 36 Initial Lumens: 2220 **Delivered Lumens:** 1350 Color Temperature: 2700K CRI: 90 Power Supply Type: Driver Power Supply Quantity: Power Supply Location: Remote TRIAC/ELV Dimming Type:

### Installation

Installation: Licensed electrician required Compatible Sloped Ceiling Compatible?: Minimum Hanging Height: 5.75 73.75" Maximum Hanging Height:

## **Shipping**

Carton 1 L x W x H: 75" X 7" X 4" Carton 1 Gross Weight: 6 LBS

### Shade

Shade 1 Material: Aluminum w/Optical Acrylic

#### Available Finishes

Available Finishes: Bright Satin Aluminum (.16), Satin Black (.25), Satin White (.03)

### **General Listings**

Features: Certification: Color/Finish: Damp Rated C-ETL-US Satin White (.03)