COVENTRY Handlesets Entry (Egg)

Specifications

Latch Type	2-Way Latch & Universal Latch available			
Door Prep	Cross bore 2-1/8" dia (54mm). Edge bore 1" dia (25mm)			
Backset	Adjustable to 2-3/8" or 2-3/4"			
Door Thickness	1-3/8" - 1-3/4" door standard			
Cylinder	5-pin High Security - removable core			
Faceplate	1" x 2-1/4" radius corner. (Square and drive-in also available on Universal)			
Strike	Standard radius corner . Other options available.			
Latch Bolt	(Full 1/2" throw Handleset), (Full 1" throw Deadbolt). Nickel plated.			
Door Handing	Non-handed. Reversible for Left or Right hand doors.			
Keyway	KW1			

KD - keyed different

ত ž

2-12"

Keyway

Keyed Alike

Dimensions

2-7/16" 2-5/8"



2-3/8"~2-3/4"

2-3/8"~2-3/4"

1



0

Warranty & Compliances

2-5/8"

	- Limited Lifetime Mechanical / Europ Finish	spels Alle			1
Warranty	Limited Lifetime Mechanical / 5 year Finish	GRADE 3	LIFETIME		
ANSI/BHMA	Meets ANSI Grade 3 specification	Decification	Harant	YEAR LA	
ADA	N/A	Ŭ	•	Ŭ	
UL	N/A				

Order Codes

View Pack Satin Nickel (US15) Oil Rubbed Bronze (US10B)

Universal 750208 740928 750232 741009

2W

2-7/16"

TRU

-11/16"

Type:

Job: Order Code: Approvals:

Design House reserves the right to make changes in materials, specifications & models at any time. Design House also reserves the right to discontinue product without notice or obligation

