Mercury ceiling 3000K 2-wire dimming

1366118A



Design By Ross Lovegrove

Collection —



Colors & Finishes

Polished Aluminum (Pebbles)

Stainless Steel (Reflector)

Materials =

- Lighting units in die-cast aluminum
- Reflective units made of injection-molded thermoplastic material with metallic finish
- Reflector in stainless steel

Specifications	
Delivered lumens	2692lm
Light output ratio	46lm/W
Power consumption	58W
Led type	2X27W C.O.B.*
CCT (Correlated Color Temperature)	3000K
CRI (Color Rendering Index)	>93
Life expectancy	50000Hrs
Control type	Dimmable 2-Wire**
Input Voltage	120-277V
Driver	HATCH - 2 x XTC32-0700P-UNV-I


SPECIFICATIONS

**Reverse or forward phase (120v only)

Features & Accessories


• Custom applications available

Dimensions =



Light distribution -

Indirect



Red = Max Cd. Through Vertical plane Blue = Max Cd. Through Horizontal plane

Luminaire weight

40.26 lbs / 18.26 kg

Warranty 5 year limited warranty

Artemide

Packaging

1 Box

1 x 47-5/16" x 47-5/16" x 9-15/16" / 57.54 lbs - 120 cm x 120 cm x 25 cm / 26.1 kg