

# NIVEOUS - LED Pendant

PD-52307, PD-52310, PD-52313

# dweLED

by WAC Lighting



Fixture Type:

Catalog Number:

Project: \_\_\_\_\_

Location: \_\_\_\_\_

## PRODUCT DESCRIPTION

The perfect sphere.

## FEATURES

- Mouth blown etched opal glass provides even illumination
- Integral swivel for sloped ceiling
- Driver located in standard 4" junction box
- Three 12" and one 6" downrods included (additional downrods available)
- 2.95" x 1.88" x 1.14" universal driver (120V - 220V - 277V)
- Color Temperature: 3000K (2700K/3500K special order)
- CRI: 90
- Rated Life: 70,000 hours
- Supplied with 114" of wire

## SPECIFICATIONS

**Construction:** Aluminum with acrylic diffuser




**Input:** 120V - 277V

**Dimming:** 100% - 10% ELV

**Light Source:** High output LED

**Finish:** Brushed Nickel (BN), White (WT), Aged Brass (AB)

**Standards:** ETL/cETL, Damp location listed



\*Driver installs within junction box

## ORDER NUMBER

| Model           | Size | Watt | LED Lumens | Delivered Lumens | Finish                          |
|-----------------|------|------|------------|------------------|---------------------------------|
| <b>PD-52307</b> | 7"   | 10W  | 777        | 588              | <b>BN</b> <i>Brushed Nickel</i> |
| <b>PD-52310</b> | 10"  | 14W  | 906        | 685              | <b>WT</b> <i>White</i>          |
| <b>PD-52313</b> | 13"  | 14W  | 906        | 715              | <b>AB</b> <i>Aged Brass</i>     |

Example: **PD-52310-BN**

For 2700K option, add "-27"; 3500K add "-35" before the finish: **PD-52310-27-BN**

dweLED.com  
Phone (800) 526.2588  
Fax (800) 526.2585

**Headquarters/Eastern Distribution Center**  
44 Harbor Park Drive  
Port Washington, NY 11050

**Central Distribution Center**  
1600 Distribution Ct  
Lithia Springs, GA 30122

**Western Distribution Center**  
1750 Archibald Avenue  
Ontario, CA 91760