


Project:

## Spec Sheet

Description: Compact luminaires direct light down from the pure geometry of a triangular prism. Also available as a [Sconce](#), [Panel Sconce](#), [Bollard](#), and [Double Bollard](#).

Type #:



### Dimensions

Height:	4.5"
Width:	3.5"
Extends:	2.5"
Minimum Extension:	2.5"
Maximum Extension:	2.5"
Canopy/Backplate/Base Width:	3
Canopy/Backplate/Base Depth:	0.5
Canopy/Backplate/Base Height:	4.25

### Electrical Specs

Bulb(s) Included?:	Yes
Bulb 1 Type:	Integral LED
Bulb Quantity:	1
Input Voltage:	120VAC
Wattage:	10
Initial Lumens:	980
Color Temperature:	3000K
CRI:	90
Power Supply Type:	Transformer
Power Supply Quantity:	1
Power Supply Location:	Outlet Box
Dimming Type:	ELV
Bulb Max Wattage:	10

### Installation

Installation:	Licensed electrician required
Installation Orientation:	Vertical

### Shipping

Carton 1 L x W x H:	6" X 7" X 6"
Carton 1 Gross Weight:	2 LBS
Fixture Weight:	1

### Shade

Shade 1 Material:	Diecast Aluminum
-------------------	------------------

### Available Finishes

Available Finishes: Textured Bronze (.72), Textured Gray (.74), Textured White (.98)

### General Listings

Features:	Wet Rated
Certification:	C-ETL-US
Color/Finish:	Textured Gray (.74)
Dark Sky Friendly:	Y