

Specifications

DESCRIPTION

- Metal construction with various finishes identified by suffix
- Flexible supplies with 3/8" compression fittings
- Includes side spray with Duralock[™] quick connect system

OPERATION

- Lever style handle
- Operates with less than 5 lbs. of force

FLOW

• Aerator is limited to 1.5 gpm max (5.7 L/min)

CARTRIDGE

- 1255[™] Duralast[®] cartridge for Single-Handle Faucets
- Nonmetallic/nonferrous and stainless steel material

STANDARDS

- Third party certified to ASME A112.18.1/CSA B-125.1 and all applicable requirements referenced therein
- Certified to NSF 61/9 & 372
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- ADA for lever handle

WARRANTY

- Limited lifetime warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations



Belfield™ Single Handle Lever Kitchen Faucet

Model: 7240 series less Side Spray

Model: 7245 series with Side Spray

NOTE: 7240 SERIES IS DESIGNED TO INSTALL THROUGH 1 HOLE OR 3 HOLES 1-1/4" (32mm) MIN. DIAM. AND 4" (102mm) ON CENTER.

NOTE: 7245 SERIES IS DESIGNED TO INSTALL THROUGH 2 HOLES OR 4 HOLES 1-1/4" (32mm) MIN. DIA. AND 4" (102mm) ON CENTER.

