
SELECTING YOUR DOWNROD LENGTH

Complete catalog number by selecting your downrod length, then adding the finish code to the model number.

٠



1.	Choose	downrod	length
----	--------	---------	--------

2. Choose downrod finish

2.5" =	CFDR25 ¹	36" = CFDR 3
12" =	CFDR1	48" = CFDR4
18" =	CFDR18	60" = CFDR5
24" =	CFDR2	70" = CFDR 70

See chart below for finish color codes

 $^{\rm 1}$ Only certain fan models accommodate with the 2½" downrod.

CFSCKXXX - SLOPED CEILING KIT (UP TO 45°)



- For use on cathedral and sloped ceilings up to 45°
- Features a screw-in safety strap to lock the hanger ball in place
- Complete catalog number by adding the finish code to the model number. See chart above.
- Shown in GRT. Also available in AB, AP, AW, BQ, BS, GBZ, GES, ORB, PT, SW, VNB, VS and WW
- For use with horseshoe receivers: RC188 and RCK55 •

Our standard hanging system can be used for sloped ceilings up to 26° and 5/12 pitch ceiling.

CFDC - DOWNROD COUPLER



- Connect (2) or more downrods for taller ceiling applications.
- Shown in BS. Also available in AB, AP, AW, BQ, GBZ, GES, GRT, ORB, PT, SW, VNB, VS and WW



- closer to the ceiling
- In most instances you will save at least 2" of space if you bring your fan closer to the ceiling
- Shown in WW. Also available in AB, AP, AW, BQ, BS, GBZ, GES, GRT, ORB, PT, SW, VNB, and VS

