

Project:

## Thin-Line LED Pendant Spec Sheet

SKU: 2816.16-6 Learn more at:

https://sonnemanlight.com/thin-line-led-pendant

Description:

A system of minimally scaled LED linear pendants, uplight/downlight wall bars, and indirect light wall bars, Thin-Line is offered in a variety of lengths, finishes, and lighting configurations. Thin-Line pendants are available in single- and double-sided configurations; the single-sided configurations can be installed as a downlight or up-light, providing direct or indirect illumination. Our Optional Mini Box Canopy is also available for the Thin-Line LED Pendant.

Type #:



#### **Dimensions**

Height: 5"
Width: 72"
Length: 0.75"
Canopy/Backplate/Base: 4.5"
Hanging Details: 6' Adjustable Cord

Size: 6' One-Sided

Canopy/Backplate/Base Height: 0.5

# **Electrical Specs**

Bulb(s) Included?: Integral LED Bulb 1 Type: **Bulb Quantity:** Input Voltage: 120VAC Wattage: 36 Initial Lumens: 2220 **Delivered Lumens:** 1350 3000K Color Temperature: CRI: 90 Power Supply Type: Driver Power Supply Quantity: Power Supply Location: Remote Dimming Type: TRIAC/ELV Bulb Max Wattage: 36

### Installation

Installation:

Licensed electrician required

Sloped Ceiling Compatible?:

Minimum Hanging Height:

Maximum Hanging Height:

73.75"

# Shipping

Carton 1 L x W x H: 75" X 7" X 4"
Carton 1 Gross Weight: 6 LBS

### **Shade**

Shade 1 Material: Aluminum w/Optical Acrylic

#### **Available Finishes**

Available Finishes: Bright Satin Aluminum (.16), Satin Black (.25), Satin White (.03)

### **General Listings**

Features: Certification: Color/Finish:

Dark Sky Friendly:

Damp Rated C-ETL-US Bright Satin Aluminum

(.16)