

Features

- 12" (305 mm) rough-in
- Polished chrome trip lever
- Less seat and supply
- Vitreous china
- 1.0 gpf (3.8 lpf)
- Equipped with Sloan FLUSHMATE_® Sloan_® Valve Company
- Combination toilet
- Optional bedpan lugs or tank cover locks
- Elongated bowl
- 11-1/2" (292 mm) x 9-1/2" (241 mm) water area
- 30-1/8" (765 mm) x 21-1/4" (540 mm) x 29-1/4" (743 mm)

Codes/Standards Applicable

Specified model meets or exceeds the following:

- ASME A112.19.2/CSA B45.1
- EPA WaterSense



Colors/Finishes

- 0: White
- CP: Polished Chrome
- $\bullet \ \mbox{PB: Vibrant}_{\ensuremath{\mathbb{R}}} \ \mbox{Polished Brass}$
- Other: Refer to Price Book for additional colors/finishes

Model	Description	Trip Lever	•	Colors/Finishes				
K-3531	Elongated bowl toilet	left-hand		0	Othe	r		
K-3531-RA	Elongated bowl toilet	right-hand		0	Othe	r		
K-3531-T	Elongated bowl toilet with tank cover locks	left-hand		0	C Othe	r		
K-3531-TR	Elongated bowl toilet with tank cover locks	right-hand		0	D Othe	D Other		
Recommended Accessories								
K-4664	Brevia™ seat with cover		0 🗆			□ Other		
K-7637	Angle supply with stop – 3/8" NPT			CP	D PB	Other		

Specified Model

Product Specification

The elongated combination toilet shall be made of vitreous china. Toilet shall be 30-1/8'' (765 mm) in length, 21-1/4'' (540 mm) in width, and 29-1/4'' (743 mm) in height with a 11-1/2'' (292 mm) x 9-1/2'' (241 mm) water area. Toilet shall be 12'' (305 mm) rough-in and less seat and supply. Toilet shall include a polished chrome trip lever. Toilet shall have a 1.0 gal (3.8 L) per flush. Toilet shall be equipped with Sloan Flushmate_® - Sloan Valve Company. Toilet shall have optional bedpan lugs or tank cover locks and available with right or left hand trip lever. Toilet shall be Kohler Model K-3531-_____.

Page 1 of 2 1054184-4-**F**



WELLWORTH_®

PRESSURE LITE_® 1.0 TOILET K-3531

WELLWORTH®

Technical Information

Fixture:			
Configuration	Two-piece, elongated		
Water per flush	1.0 gpf (4.0 lpf)		
Passageway	2-1/4" (57 mm)		
Water area	11-1/2" (292 mm) x 9-1/2" (241 mm)		
Water depth from rim	5-5/8" (143 mm)		
Seat post hole centers	5-1/2" (140 mm)		
Maximum static pressure required	35 psi (241 kPa)		
Maximum static pressure	80 psi (551.6 kPa)		

Included components*:				
Bowl	K-4303			
Tank	K-4484			
Tank cover	1036375			
Bolt cap accessory pack	52048			
Tank accessory pack	73062			
Trip lever, left-hand	K-9481-L			
Trip lever, right-hand	K-9481-R			
* Equipped with Sloan Flushmate _® - Sloan Valve Company				

Installation Notes

Install this product according to the installation guide.



Product Diagram

