

Project:

Thin-Line LED Pendant Spec Sheet

SKU: 2816.25-8 Learn more at:

 $\underline{\text{https://sonnemanlight.com/thin-line-led-pendant}}$

Description:

A system of minimally scaled LED linear pendants, uplight/downlight wall bars, and indirect light wall bars, Thin-Line is offered in a variety of lengths, finishes, and lighting configurations. Thin-Line pendants are available in single- and double-sided configurations; the single-sided configurations can be installed as a downlight or up-light, providing direct or indirect illumination. Our Optional Mini Box Canopy is also available for the Thin-Line LED Pendant.

Type #:





Dimensions

 Height:
 5"

 Width:
 96"

 Length:
 0.75"

 Canopy/Backplate/Base:
 4.5"

 Hanging Details:
 6' Adjustable

Cord Size: 8' One-Sided

Canopy/Backplate/Base Height: 0.5

Electrical Specs

Bulb(s) Included?: Integral LED Bulb 1 Type: **Bulb Quantity:** Input Voltage: 120VAC Wattage: 47 Initial Lumens: 3120 **Delivered Lumens:** 1800 3000K Color Temperature: CRI: 90 Power Supply Type: Driver Power Supply Quantity: Power Supply Location: Remote Dimming Type: TRIAC/ELV Bulb Max Wattage:

Installation

Installation:

Licensed electrician required

Sloped Ceiling Compatible?:

Minimum Hanging Height:

Maximum Hanging Height:

73.75"

Shipping

Carton 1 L x W x H: 99" X 7" X 4"
Carton 1 Gross Weight: 7 LBS

Shade

Shade 1 Material: Aluminum w/Optical Acrylic

Available Finishes

Available Finishes: Bright Satin Aluminum (.16), Satin Black (.25), Satin White (.03)

General Listings

Features: Certification: Color/Finish:

Dark Sky Friendly:

Damp Rated C-ETL-US Satin Black (.25)