
LED Pendant



| Fixture Type: | |
|---------------|----|
| • | |
| Catalog Numbe | r: |
| | |
| Project: | |

Location:



PRODUCT DESCRIPTION

A cleverly executed open metal shade that illuminated when suspended without revealing hidden light sources. A frosted acrylic diffuser conceals the high powered LEDs within the brushed aluminum spun metal shade, preserving an open to the ceiling mystique. This Inverted Pendant is suspended on three thin low profile cables without the need for an additional power cord, lending to a simple and minimalistic design. Adjustable to lengths of 120" through a push-pin locking mechanism at the canopy.

FEATURES

- Frosted acrylic diffuser conceals LEDs within the shade, preserving an open to the ceiling mystique
- · Driver located inside canopy
- Features up & down light
- Cable suspension carrying low voltage may be field shortened
- Universal driver (120V-220V-277V)
- Color Temp: 3000K
- CRI: 80

 \bullet Dimming: 100% - 5% ELV or 0-10V

Rated Life: 83,000 hoursInput: 120 - 277VORDER NUMBER

SPECIFICATIONS

Construction: Die cast Aluminum and Frosted Acrylic Diffuser

Light Source: High output LED.

Finish: Brushed Aluminum

 $\textbf{Standards:} \ \mathsf{ETL} \ \& \ \mathsf{cETL} \ \mathsf{damp} \ \mathsf{location} \ \mathsf{listed}.$

| | Watt | LED Lumens | Delivered Lumens | Finish |
|-----|-------|------------|------------------|------------------|
| 18" | 33.5W | 2450 | 1755 | Brushed Aluminum |
| 24" | 43W | 3235 | 2385 | |