

Project: _____
Fixture Type: _____
Location: _____
Contact: _____

LED FLUSH MOUNT

Ceiling mounted • Damp location listed



Specifications:

Description:

One-light LED Flush Mount

Construction:

- Brushed Nickel
- Steel construction
- Glass: Etched
- LED Module is replaceable
- Dimming to 10% brightness with most triac type dimmers
(See Dimming Notes)
- Meets California T24 JA8 requirements
- Unit covers a standard 4" hexagonal recessed outlet box
- Mounting plate for outlet box included
- 6" of wire supplied

Performance:

Number of Modules	1
Input Power	25W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	2015/81 (LM-79) per module
CCT	3000K
CRI	90+
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Labels	cCSAus Damp location listed
	ENERGY STAR® qualified [pending]

Images:



Dimensions:

Diameter: 12-9/16"
Height: 4-1/2"

Draft

Final performance is being validated through lab testing - ENERGY STAR will not be in effect until testing / certification is completed.

Catalog number:

Finish	Color Temp	CRI
Brushed Nickel	30	90 CRI

LED FLUSH MOUNT

Ceiling mounted • Damp location listed



Dimming Notes:

This product is designed to be compatible with many triac (forward-phase) controls.

The following is a partial list of known compatible dimmer controls:

Forward-Phase Controls

Lutron	(Part Number NTELV-300)
Leviton	(Part Number 6681)
Leviton	(Part Number 6672)
Leviton	(Part Number 6674)
Lutron	(Part Number AYCL-153P)
Lutron	(Part Number AYLV-600P)
Lutron	(Part Number NTLV-600)
Lutron	(Part Number MAELV-600)
Lutron	(Part Number AWRMG-EAW)
Lutron	(Part Number N-600)

Digital type dimmers are not recommended.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.
Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.