

Project:

Fixture Type:

Location:

Contact:

Ceiling mounted • Damp location listed

Description:

This 54" two-blade outdoor ceiling fan combines a sleek, contemporary style with high-quality performance. A wire frame supports canvas wrapped blades that feature UV inhibitors to protect the fabric from fading in the sunlight. Three fan speeds and a reversible switch keep individuals cool in the summer and warm in the winter. A white opal glass shade contains an 18W LED module light kit, offering energy efficient and cost savings benefits.

Specifications:

- Architectural Bronze (painted)
- Steel construction
- White Opal Plastic Flat Round
- This 54" two-blade outdoor ceiling fan combines a sleek, contemporary style with high-quality performance
- A wire frame supports Canvas wrapped blades that feature UV inhibitors to protect the fabric from fading in the sunlight
- Warm Mushroom Canvas blades
- Rich Architectural Bronze finish
- Refresh your indoor or covered outdoor living spaces with the crisp, clean style of this 54" fan
- The Two blade fan features an all-weather damp location rating to accommodate a variety of settings throughout the home
- White opal shatterproof shade with a 18W dimmable LED light source offers a warm 3000K-color temperature, 90 CRI and 1400 lumens
- A hand held remote control with fan speed control and full range light dimming is included and comes with a convenient wall bracket for storage
- Features modern styling for Contemporary, Mid-Century Modern living spaces
- Reversible motor for year round comfort allows you to choose either a down drafts (summer) or an up draft (winter)
- As a general rule of thumb, lighting experts suggest this fan is ideal in a room size that ranges from 226- to 400-square feet
- A 1"x 6" downrod is included. Longer accessory downrods can be ordered separately
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting Yes for outlet box included
- 80" of wire supplied
- Mushroom blades, canvas construction
- 20 blade pitch
- Full function remote included
- Triple capacitor speed control, manual reverse control Speed, Manual Reverse
- Airflow: 4371 CFM*
- Energy consumption: 65 watts (excluding lights)*
- Airflow efficiency: 67 cfm/watt*
- * Fan on a downrod

Performance:

Number of Modules	1
Input Power	18w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1400/77 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50,000 (L70/TM-21)
Warranty	Limited Lifetime
Labels	ULus Damp location listed

Images:



Dimensions:

Diameter: 54"
Height: 14-7/8"

Glass
Width: 7-1/4"
Height: 2"

Dimming Notes:

This collection is designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

Lutron - NTEVL-300

Lutron - DVELV-300P

Lutron-DVCL-253P

Lutron - Caseta Wireless

IDevices - IDEV009

Leviton – 6672

Leviton – 6674

Lutron - AYCL-153P

Lutron - TGCL-153-PH-WH

Lutron - AYL-600P

Lutron - MAELV-601

Leviton -AWSMT-EAW

Lutron - N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.
Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.