

## **LED Outdoor**





## **PRODUCT DESCRIPTION**

Light projection tuned with precision, this collection is a discrete cylinder with minimal mounting hardware. Available in a single or double light configuration which can be mounted both vertically and horizontaly. The light engine is factory sealed for maximum protection against the harshest elements.

## **FEATURES**

- Discrete cylinder with minimal mounting hardware
- Up & down light
- Light engine is factory sealed for maximum protection from the elements
- Can be mounted vertically or horizontally
- Solid aluminum construction
- Driver located in standard 4" junction box
- Universal driver (120V-220V-277V)
- Color Temp: 3000K
- CRI: 90

Dimming: 100% - 10% ELVRated Life: 72,000 hoursInput: 120 - 277V

0	R	n	F	R	NII	17	M	R	F	R

	Watt	LED Lumens	Delivered Lumens	Finish
10"	11W	735	485	Brushed Aluminum Bronze
14"	21W	1500	1080	Black

Fixture Type:	
Catalog Numbe	r:
Project:	
Location:	

## **SPECIFICATIONS**

Construction: Aluminum and White Diffuser Lens

**Light Source:** High output LED.

Finish: Brushed Aluminum, Black, Bronze

Standards: ETL & cETL wet location listed. IP 65. CEC Title 24