


Submitted Model No.:______Specific Features:



▲ Designate proper finish suffix



see what Delta can do



- 2-In-1 Shower
- 5-Spray Setting Hand Shower
- Certified Dual Check Valves

FEATURES:

■ Touch-Clean® Nozzles

STANDARD SPECIFICATIONS

- Max flow rate 1.75 gpm @ 80 psi, 6.6 L/min @ 550 kPa (58569-▲-PK)
- Max flow rate 2.5 gpm @ 80 psi, 9.5 L/min @ 550 kPa (58569-▲25-PK)
- Integrated hand shower docks securely into shower head when not in use
- Multiple hand shower spray settings pause is a non-positive shut-off
- 3-Way diverter allows for single or shared operation of the shower head and hand shower
- Push button activates pause mode
- Hand shower lever changes spray modes
- 60"-82"(1524-2083 mm) stretchable metal hose

WARRANTY

- Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.
- Electronic Parts and Batteries (if applicable) –
 5 years from the date of purchase; or for commercial purchasers, 1 year from the date of purchase. No warranty is provided on batteries.
 No warranty is provided on batteries.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1 ◆
- EPA WaterSense® Applies to 58569-▲-PK only
- Your Delta Faucet hand shower incorporates a backflow protection system that has been tested to be in compliance with ASME A112.18.3, CSA B125.1 and ASME A112.18.1. It incorporates two certified check valves in series, which operate independently and are integral, non-serviceable parts of the wand assembly.

Delta Faucet Company

55 E. 111th Street, Indianapolis, IN 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2020 Delta Faucet Company