Installation manual for:

Dimensions:W12" H16" E8.5" L3 Bulb Type:E12 bulb not included Lamp Frame Weight(lbs):3.2 Total Weight(lbs):13





Step 1

Frame Assembly Diagram

SAFETY


Warning: MAKE SURE THE ELECTRICITY TO THE WIRES YOU ARE WORKING ON IS SHUT OFF BY EITHER REMOVING THE FUSE OR TURNING OFF THE CIRCUIT BREAKER.

CAUTION

- Before assembling the lighting fixture, please read all instructions carefully.
- All frame & crystal components are fragile, please handle with care.
- Required supply circuit:110 130V/60Hz
- Labeled wires are "L" for live wire, "N" for neutral wire, "E" for ground wire.
- Never install fixture on damp ceiling, the room should be dry and well ventilated

(01)

- All electrical components must be installed by a licensed electrician and in accordance with the National Electrical Code and the appropriate local electrical codes.



(02)

″ L3

Please use the parts list to ensure you are not missing any parts


		PARTS LIST	
part	picture	Description	Qty
ZA	No Contraction of the second s	Junction box not included	1
ZB		4"Crossbar	1
ZC		4.7"Back plate	1
ZD		Knurled nut	2
P1		4"Candle cover	3
P2		Bobeche 4.5"	3
Р3		Lamp arm	1
А	Å	1050-14#+911-50#	15
В	*	1050-14#*2+911-63#	2
С		1050-14#+911-63#	2
D_	***	1050-14#*6+911-63# 1	

part	picture	Description	Qty	Check list
E		1050-14#*4	1	
F	***	1050-14#*10	1	
G	Å	1050-14#+63#	1	

(01)

Step 2

Canopy installation instructions




Important: Test sockets with bulb before dressing the fixture.

- 1. Attach the Crossbar(ZB)to the Junction Box(ZA)using the two crossbar screws(ZC)which are not supplied and should already be in your box.
- 2. Be sure when connecting the wire use electrician approved junction caps(ZG).
- 3. Stow the excess wire in the junction box(ZA).
- 4. Crossbar Bracket(ZE), attach Wall Lamp Bass(ZD) to the awall.

(04)

Frame Assembly Diagram





Step 3

Frame Assembly Instructions

Installation:

Please read all instructions carefully.Before you proceed to install, make sure that the power supply is turned off and remains off until installation is complete.

Please note that each part has been assigned a number. Please proceed in a numerical order.

- 1. Fix the crossbar (01) on the installation 4" junction-box(J-box).
- 2. Make sure the positive and negative charges of wire and lamp
 - body match correctly, screw the connect point with the junction cap.
- 3. Make sure the main wire is enough long and keep the rest wire in the 4" J-box.

4. Fix the lamp body (02) on the crossbar (01) with crossbar bracket (03).5. Put the metal tube through the central hole in the glass dish (04) and place the glass plate on the fixer under

6. As the crystal dressing instruction, hang the crystal parts

The end!


Step 4 Crystal Dressing Instructions

(07)

 Hang crystal "A", "B", "D"
Connect both ends of F with A, Connect both ends of E with C.

Crystal Dressing Diagram

When dressing the chandelier with the crystals please remember to wear either rubber or cotton gloves. So as to prevent any damage or smudging on the crystals.



 $(\mathbf{08})$

Cleaning and Maintenance of Chandelier Frame The finish on our chandelier frames and fixture frames is protected by a durable coating of lacquer. To clean, use a clean, soft, dry cloth. Do not use any metal polishes, cleaners, abrasives or any substance which could remove the protective finish. Failure to follow these instructions automatically voids the guarantee.

Cleaning and Maintenance of Crystals Wet a soft cotton fabric in clean warm water and wipe gently, then polish with a dry soft cotton fabric.

(10)

Elegant Lighting Warranty

The finish and frame of your new chandelier or fixture are warranted for a period of two(2) years from the date of purchase. Our company will at its option, repair or replace any frame that has a defect in the material or workmanship during the warranty period. All crystals are guaranteed for their original quality during the life of the chandelier. Breakage is not covered by this warranty.

To make a claim under this warranty, contact our customer service department at the address and phone number shown below. A written return authorization form will be sent to you with specific instructions.

Returns and Conditions of Warranty

Returns must be pre-authorized by contacting our customer service department at the address on the reverse side. Returns will only be accepted with a written return merchandise authorization and return shipping charges pre-paid. We reserved the right to inspect all returned merchandise to fully determine the nature of any defect. This guarantee shall not apply to any product that has been changed, altered or otherwise modified, nor shall it apply to any product that has been repaired or altered by anyone other than a pre-authorized facility. We will not be responsible for any breakage or damages incurred during transit, nor for crystal parts or metal frame part that have been subject to misuse, negligence, accident or inappropriate handling. Also, we will not be held responsible for damage incurred during improper installation or wiring by others, nor for damages resulting from a failure to follow the recommended maintenance or installation procedures. This guarantee is issued in lieu of any and all other guaranteed or warranty, whether written or implied and any and all other obligations or liabilities. Further, we neither authorize nor permit any other person or firm to assume for us, any liability in connection with the sale of our products.

(12)