SONNEMAN A WAY OF LIGHT

Project:

Thin-Line LED Pendant Spec Sheet

SKU: 2816.03-8 Learn more at: https://sonnemanlight.com/thin-line-led-pendant

Description:

A system of minimally scaled LED linear pendants, uplight/downlight wall bars, and indirect light wall bars, Thin-Line is offered in a variety of lengths, finishes, and lighting configurations. Thin-Line pendants are available in single- and double-sided configurations; the single-sided configurations can be installed as a downlight or up-light, providing direct or indirect illumination. Our <u>Optional Mini Box Canopy</u> is also available for the Thin-Line LED Pendant.

Type #:



Dimensions

Height:	5"
Width:	96"
Length:	0.75"
Canopy/Backplate/Base:	4.5"
Hanging Details:	6' Adjustable
	Cord

Size: Canopy/Backplate/Base Height:

Electrical Specs

Bulb(s) Included?: Bulb 1 Type: Bulb Quantity: Input Voltage: Wattage: Initial Lumens: Delivered Lumens: Color Temperature: CRI: Power Supply Type: Power Supply Quantity: Power Supply Location: Dimming Type: Bulb Max Wattage:

Installation

Installation:

Sloped Ceiling Compatible?: Minimum Hanging Height: Maximum Hanging Height:

Shipping

Carton 1 L x W x H: Carton 1 Gross Weight:

Shade

Shade 1 Material:

Available Finishes

Available Finishes: Bright Satin Aluminum (.16), Satin Black (.25), Satin White (.03)

General Listings

Features: Certification: Color/Finish:

Dark Sky Friendly:

Damp Rated C-ETL-US Satin White (.03) N

99" X 7" X 4" 7 LBS

Licensed

required

5.75

73.75"

electrician

Compatible

Aluminum w/Optical Acrylic

Yes Integral LED 1 120VAC 47 3120 1800 3000K 90 Driver 1 Remote TRIAC/ELV 47

8' One-Sided

0.5