LED Flush Mount

Features

Contemporary shallow flush mount fixture can be used in various applications including corridors, baths, laundry rooms and kitchens. Available in three sizes. Fixture mounts to a standard junction box (not included).

Construction

Housing is die formed aluminum band with bowed white diffuser. Back pan is made from 22-gauge stamped steel and painted in lighting grade white. Power supply connections must be made in a junction box (not included).

Finish Brushed aluminum trim.

Diffuser

.100" thick white acrylic bottom diffuser.

Electrical

Input 120VAC / 60 Hz. Compatible with Triac or ELV dimmers.

Integrated LED modules capable of producing: 12" - 22W, 1800 source lumens 14" - 33W, 2500 source lumens 19" - 46W, 3200 source lumens Adjustable Choice 3000K, 3500K, 4000K (CCT). Rated for 50,000 Hrs., 90 CRI.

Certification

cETLus listed for damp locations **ENERGY STAR® qualified** Title 24/JA8 Compliant


Warranty

Limited warranty: This fixture is free from defects in materials and workmanship for a period of 5 years from date-of-purchase.

Specifications and dimensions subject to change without notice.







Ordering Information:

	Source			_
LED	Lumens	Adjustable CCT	DIA.	D
22W	1800	3000K/3500K/4000K	12"	3"
33W	2500	3000K/3500K/4000K	14"	3"
46W	3200	3000K/3500K/4000K	19"	3"