merican tandard

H2OPTIMUM® SIPHONIC RIGHT HEIGHT® ELONGATED TOILET VITREOUS CHINA

BARRIER FREE

H₂OPTIMUM[®] SIPHONIC **RIGHT HEIGHT® ELONGATED TOILET**

□ 288AA.114

- Vitreous china
- Ultra high efficiency toilet (UHET) uses 4.2Lpf/1.1gpf
- Elongated siphon action bowl with direct-fed jet
- 16-1/2" rim height for accessible applicatons
- Meets EPA WaterSense® criteria
- MaP PREMIUM listed
- Includes EverClean® antimicrobial surface
- PowerWash[®] rim scrubs bowl with each flush
- 305mm (12") rough-in
- Fully glazed 2" Trapway
- Generous 9" x 8" water surface area
- Chrome finish trip lever is supplied
- Sanitary bar on bowl
- 2 color matched bolt caps
- Limited lifetime warranty on chinaware and limited five year warranty on all mechanical parts
- 288AA.115 Same as above except trip lever is on right hand side.

Separate Component Parts:

3705.216 Right Height Elongated Bowl **4133A.114** Tank

Nominal Dimensions:

756 x 380 x 800mm (29-3/4" x 15" x 31-1/2")

Fixture only, seat and supply by others

Alternative Tank Configuration Available:

□ 4133A.115 tank complete with trip lever located on right side

Compliance Certifications -Meets or Exceeds the Following Specifications:

- ASME A112.19.2/CSA B45.1
- CALGreen and California Energy Commission (CEC) Compliant
- US EPA WaterSense[®] criteria for UHETs

To Be Specified:

- □ Color: □ White
- □ Seat: American Standard #5257A.65C Easy Lift and Clean Elongated Seat with Cover and Slow Close hinges
- Alternate Seat:
- Supply with stop:



FICIENT





NOTES:

THIS COMBINATION IS DESIGNED TO ROUGH-IN AT A MINIMUM DIMENSION OF 305MM (12") FROM FINISHED WALL TO C/L OF OUTLET. * DIMENSION SHOWN FOR LOCATION OF SUPPLY IS SUGGESTED. SUPPLY NOT INCLUDED WITH FIXTURE AND MUST BE ORDERED SEPARATELY.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerance established by ANSI Standard A112.19.2 These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.



MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ICC ANSI A117.1 REQUIREMENTS FOR ACCESSIBLE AND USABLE BUILDING FACILITIES-CHECK LOCAL CODES.



© 2017 AS America Inc.