

Project: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Location: \_\_\_\_\_

Contact: \_\_\_\_\_

# LED FLUSH

Ceiling mounted • Damp location listed



## Specifications:

### Description:

One-light LED Flush Mount

### Construction:

Brushed Nickel  
Steel construction  
Glass: Etched glass bowl  
LED Module is replaceable Flicker-free dimming to 10% brightness with most ELV type dimmers  
(See Dimming Notes)  
Unit covers a standard 4" hexagonal recessed outlet box  
Mounting plate for outlet box included  
6" of wire supplied  
Brushed Nickel finish  
120V AC replaceable module  
Dimmable to 10% with Triac or ELV dimmers  
3000k color temperature  
TM-21 60,000 hour life

### Performance:

Number of Modules	1
Input Power	17W
Input Voltage	120V
Input Frequency	60Hz
Lumens/LPW	1211/71.2 (LM-79) per module
CCT	3000K
CRI	90+
Life	60,000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Labels	cCSAus Damp location listed
	ENERGY STAR® qualified

### Images:



### Dimensions:

Diameter: 11"

Height: 4"

### Catalog number:

Finish	/	Color Temp	CRI
Brushed Nickel		30	90 CRI