

Project: _____

Fixture Type: _____

Location: _____

Contact: _____

Two-Light Wall Lantern

Wall vertical only mounted • Wet location listed



Description:

Clean lines are up front and center for these modern LED outdoor sconces. This product features a die-cast aluminum frame and matte white, acrylic diffuser. Energy efficient LED source offers 3000K color temperature and 90+CRI output. Title 24 compliant. Two-light 9w LED wall lantern in a Brushed Nickel finish.

Specifications:

- Brushed Nickel (plated)
- Aluminum Construction
- Matte White acrylic diffuser
- LED Module is replaceable
- Modern LED outdoor sconce.
- Clean lines are central to design.
- Features a die-cast aluminum frame and matte white, acrylic diffuser.
- 623 lumens 69.2 lumens/watt (source)
- 3000K color temperature, 90+ CRI.
- Wall mount - vertical only.
- Dimmable to 10% brightness (See Dimming Notes)
- Chassis covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 6" of wire supplied
- Complies with "Americans with Disabilities Act" - ADA
- ENERGY STAR® qualified
- Meets California Title 24 high efficacy requirements for outdoor use only

Performance:

Number of Modules	2
Input Power	9w per module
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	623/69.2 (LM-82) per module
Lumens/LPW (Delivered)	640/41 (LM-79)
CCT	3000 K
CRI	90+
Life (hours)	60,000 (L70/TM-21)
FCC	Meets FCC Title 47, Part 15 Class B
Min. Start Temp	-30 °C
Max. Operating Temp	30 °C
Warranty	5 year warranty
Labels	cCSAus Wet location listed
	ENERGY STAR® qualified
	Meets California Title 24 high efficacy requirements for outdoor use only

Images:



Dimensions:

Width: 5-5/8"

Depth: 4"

Height: 16"

H/CTR: 8"

Glass

Width: 3-3/4"

Length: 5-3/8"

Height: 15-15/16"



Dimming Notes:

It is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls

- Lutron Nova T NTELV-300
- Lutron Vienti VTELV-600
- Lutron Ariadni AYCL-153P
- Lutron Diva DVCL-153P
- Lutron Maestro MAELV-600
- Lutron spacer/system SPSELV-600
- Leviton Renoir II AWRMG-EAW

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.