# **CODER** PL SERIES FLAT DOOR CABINET

#### Features

- Recess or surface mount
- Mirrored doors and interior
- 3-way adjustable concealed hinge system
- SAFESEAL™ gasket frame
- Rust-free aluminum construction
- Can be installed as a left- or right-hand door swing
- Three adjustable glass shelves
- 30" (76.2 cm) x 30" (76.2 cm) x 4-5/8" (11.7 cm)

#### **Codes/Standards Applicable**

Specified model meets or exceeds the following:

None applicable



**PLM3030W** 

#### **Specified Model**

Model	Description	
PLM3030W	Beveled edge, white interior	
PLM3030B	Beveled edge, black interior	
Required Acc	essories - For Surface-Mount Installations Only	
M30SKD4A	Aluminum side kit	
PLSK30	Mirrored side kit	
Refer to the P	ice Guide for additional side kit colors and finishes	
Optional Acce	ssories	

### **PL SERIES FLAT DOOR CABINET**

#### **Technical Information**

	Roughing-in opening	29-1/4″ (74.3 cm) x 29-1/4″ (74.3 cm) x 4″ (10.2 cm)
	Door opening angle	170°

#### **Installation Notes**

Install this product according to the installation guide.

When determining the height of the mirrored cabinet, ensure the mirrored door will clear all obstacles, such as a faucet. A minimum distance of 1" (2.5 cm) is required.

Secure the screws (provided) to a stud to avoid possible property and product damage. If this is not possible, anchors (provided) must be inserted before installing the screws.

Modular components can be joined horizontally. When ganging cabinets: rough opening width/height = total width/height of all cabinets and lights minus 3/4" (1.9 cm).

Recessed cabinets project 7/8" (2.2 cm) from wall.



## robern