









# **Riptide CF605**

# **MODEL FEATURES**

- 52" Blade Span
- 3 ABS Blades
- Wet Location Rated
- Integrated LED Light Fixture
- 4-Speed Remote Control
- 8" Downrod








#### PERFORMANCE SPECIFICATIONS

Speed	Airflow	Electricity Use	Airflow Efficiency	RPM
	Cubic Ft. Per Min.	Watts (Excl. Lights)	Cubic Ft. Per Min. Per Watt	Revolutions per Minute
High	4507	50	91	125
Low	1832	13.2	139	53

Blade	Accepts	Amps	LED Specifications			
Pitch	2.5" DR		Lumens	Watts	CRI	CCT (K)
Variable	N	0.5	1320	16	90	3000

Control	Receiver	Manual/Remote	Dimming	Downrod
Included	Included	Reverse Switch	Light	Length
SR401	Y	Remote	Υ	8"

## **ENERGYGUIDE INFORMATION**



Energy information listed above is a weighted average of High and Low speeds tested with downrod supplied.





## A. RIPTIDE – BARBEQUE BLACK

CF605BQ - Weather-Resistant Charcoal Blades, Opal Matte Shade

## B. RIPTIDE - GRAPHITE

CF605GRT - Weather-Resistant Driftwood Blades, Opal Matte Shade

## c. RIPTIDE - OIL RUBBED BRONZE

CF605ORB - Weather-Resistant Aged Oak Blades, Opal Matte Shade

# D. RIPTIDE – SATIN WHITE


CF605SW - Weather-Resistant Satin White Blades, Opal Matte Shade



E. Shown in Satin White with Weather-Resistant Satin White Blades and Opal Matte Shade

SHIPPING SPECIFICATIONS: Carton Weight: 22.71 LBS | Length: 24.7" | Width: 14.80" | Depth: 12.00"

# **Product Dimensions & Weight**



- A. Total Fan Height: 18.4"
- B. Bottom of Blade to Ceiling: 17.5"
- C. Width of Housing: 8"
- D. Width of Canopy: 7.5"

Motor Size (mm): 153 x 20 Product Weight: 19.4 LBS

# Included



#### SR401 4-Speed Remote Control

## **Recommended Accessories**



**OPTIONAL** No-Light Plates