Project:	
- - ixture Type:	
_ocation:	
Contact:	

LED CTC

Ceiling mounted · Damp location listed





Specifications:

Description:

One-light LED CTC w/DC LED Module

Construction:

Urban Bronze

Steel construction

Glass: White acrylic diffuser

Flicker-free dimming to 10% brightness with most ELV type dimmers

(See Dimming Notes)

Unit covers a standard 4" hexagonal recessed outlet box

Mounting strap for outlet box included

6" of wire supplied

Urban Bronze finish

120V AC replaceable module

Dimmable to 10% with ELV dimmers

3000k color temperature

TM-21 60,000 hour life

Performance:

Number of Modules	
Input Power	23W
Input Voltage	
Input Frequency	60Hz
Lumens/LPW	/ (LM-79) per module
CCT	3000K
CRI	90
Life	(L70/TM-21)
EMI/RFI	FCC Title 47 Part 158 Class B, ICES-003 Class
В	
Min. Start Temp	-30° C
Max. Operating Temp	30° C
Warranty	5 year warranty
Labels	cULus Damp location listed
	ENERGY STAR® qualified

Images:



Dimensions:

Diameter: 14" Height: 3-3/4"

Catalog number:

Finish	Color Temp	CRI
Urban Bronze	3000K	90 CRI