

STUDIO[®] S TWO-HANDLE WIDESPREAD LAVATORY FAUCET



GENERAL DESCRIPTION:

Cast brass valve bodies with flexible hose connections for 6" to 12" (152 mm to 30 5mm) installations. 1/4 turn washerless ceramic disc valve cartridges. Cast brass spout. Cast brass inlet shanks and 24" stainless steal braided flexible supply hoses with 3/8" compression connectors. 20 inch (500 mm) long flexible stainless steel drain cable is pre-assembled to faucet body. Metal Speed Connect[®] drain body with 1-1/4 inch (32 mm) tail piece. 1.2 gpm/4.5 L/min. maximum flow rate.





ADA COMPLIANT

WATERSENSE® CERTIFIED

PRODUCT FEATURES:

Brass Construction: Durable. Easy to clean. Ideal for prolonged contact with water. Provides the finest surface for application of colors and finishes.

Ceramic Disc Valve Cartridge: Assures a lifetime of smooth handle operation and drip-free performance.

Exclusive Speed Connect Metal Drain:

- Fewer parts. Installs in less time.
- No adjustments required seals the first time, every time.
- Flexible stainless steel cable installs effortlessly in tight spaces.

Lead Free: Faucet contains $\leq 0.25\%$ total lead content by weighted average.

SUGGESTED SPECIFICATION

Two-handle widespread lavatory faucet shall feature cast brass valve bodies with flexible hose connections for 6" to 12" installations. Shall also feature 1/4 turn washerless ceramic disc valve cartridges. Shall also feature a metal drain body with stainless steel cable actuation. Fitting shall be American Standard Model #7105.8X1.___.

American Standard

STUDIO[®] S **TWO-HANDLE WIDESPREAD LAVATORY FAUCET**

CODES AND STANDARDS

These products meet or exceed the following codes and standards:

ANSI A117.1 ASME A112.18.1 CSA B125.1 NSF 61/Section 9 **NSF 372**



		Finish Options		
Dreduct		Polished Chrome	PVD Brushed Nickel	Matte Black
Product Number	Description	002	295	243
7105.801	Studio S Widespread with metal Speed Connect® pop-up drain.	A		
7105.821	Studio S Widespread with metal Speed Connect [®] pop-up drain.	A		

ADA Meets the American Disabilities Act Guidelines and ANSI A117.1 Requirements for the physically challenged.