INSTALLATION INSTRUCTIONS

For Model # N6109 (Rev. 05/25/2007)

WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.

MOUNTING THE FIXTURE 2X(dw (A-19)

- 1. Shut off power at the circuit breaker and remove old fixture from ceiling, including the crossbar.
- Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
- Attach the Crossbar (A) to the Junction Box using the two Junction Box Screws (B). The side of the Circular Strap marked "GND" must face out.
- 4. Thread the Nipple (C) part way into the center hole of the Crossbar (A).

CONNECTING THE WIRES (Fig.2)

- 5. While holding the Light Assembly (D) towards the ceiling, connect the electrical wires as shown in Fig.2. Making sure that all wire connectors are secured. You may wrap the connections with electrical tape. If your outlet has a ground wire (green or bare copper), connect the fixture's Ground Wire to it. Otherwise, connect the fixture's Ground Wire directly to the Crossbar using the Green Screw provided. After wires are connected, tuck them carefully into the ceiling Junction Box.
- 6. Finish mounting the fixture by placing the Light Assembly (D) over Nipple (C) and secure it against ceiling with Nut Ball (F).
- 7. Install the light bulbs in accordance with fixtures specifications. CAUTION: Do not exceed the maximum wattage rating!

GLASS DIFFUSER INSTALLATION (Fig.1)

- 8. Insert the Glass Diffuser (G) into the Metal Frame (I).
- Finish mounting the fixture by aligning the three points (H) on the Metal Frame (I) with three slots (E) on the Light Assembly (D) and twisting it counter clockwise until snug as shown in (Fig.1).

Your installation is now complete. Return power to the junction box and test the fixture.

Note: Illustration (Fig.1) on this manual is for installation purposes only. It may or may not be identical to the fixture purchased.







