

Baby Devoro[™] FloWise[®] 10" High Elongated Toilet

Baby Devoro™ FloWise[®] 10" High Elongated Toilet

2315.228

- Vitreous china
- High Efficiency, Low Consumption (4.8 Lpf / 1.28 gpf)
- Meets definition of HET (High Efficiency Toilet)
- 10-1/4" rim height
- 10" roughing-in
- Elongated siphon action bowl
- Chrome trip lever
- · Sanitary dam on bowl
- Fully glazed trapway
- 2 color-matched bolt caps
- ADA and TAS Compliant
- □ 3128.001 Elongated Bowl with bolt caps
- □ 4019.228 Tank complete with coupling components and tank trim (1.28gpf / 4.8Lpf)

Nominal Dimensions:

633 x 439 x 622mm (25" x 17-1/4" x 24-1/2")

Alternative Tank Configurations Available:

- □ 4019.613 Tank with locking device complete with coupling components and tank trim
- □ 4019.828 Tank complete with trip lever on right side

Fixture only, seat and supply are not included and must be purchased separately.

Compliance Certifications -

Meets or Exceeds the Following Specifications:

 ASME A112.19.2-2008 / CSA B45.1-08 for Vitreous China Fixtures

System MaP* Score:

- 500 grams of miso @ 1.28 gpf
 - * Maximum Performance (MaP) testing performed by IAPMO R&T Lab. MaP Report conducted by Veritec Consulting, Inc. and Koeller and Company.

To Be Specified:

- □ Color: □ White
- Seat: #5001G.055 Baby Devoro Seat open front with EverClean[®] less cover
- □ Supply with Stop:





NOTES:

THIS COMBINATION IS DESIGNED TO ROUGH-IN AT A MINIMUM DIMENSION OF 254mm (10) FROM FINISHED WALL TO C/L OF OUTLET * DIMENSION SHOWN FOR LOCATION OF SUPPLY IS SUGGESTED. SUPPLY NOT INCLUDED AND MUST BE ORDERED SEPARATELY.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI Standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

