

SPRING UNIT:	All springs are heated high carbon steel. The spring unit is constructed of 13 1/2 gauge wire. This unit features a 3 3/4" four turn Bonnell type coil.
INSULATION:	A .9 oz. per square foot Densified Low melt fiber insulator pad is wrapped around the edges of the spring and stapled to the top and bottom with clinch staples. The pads are needle punched for increased strength and wear.
UPHOLSTERY:	The quilt top is flanged and stapled to the spring unit on all sides to keep it securely in place. One layer of 1.5 oz. Low melt fiber is stapled to the sleeping surface for added comfort.
QUILTING:	One layer of 1 oz. Low Melt Fiber is multi-needle quilted to the damask cover on the sleeping surface to give the mattress a deep quilted look and feel. The borders are also multi-needle quilted to .75 oz. Low Melt Fiber.
BOTTOM:	The material used on the bottom of the mattress is color coordinated with the damask ticking. It is stitch bonded material which is non-skid and abrasion resistant.
LABEL:	A professionally designed label is sewn onto the quilt top.
HEIGHT:	The overall crown height is 6 1/4" with a plus or minus of 1/2"
COIL COUNT:	Queen - 299 Reg. - 253 37" Twin - 184 Chair - 161
CONSTRUCTION:	All material edges are serged for additional strength and to prevent seam slippage. 1 1/4" color coordinated binding tape is used to enclose the mattress on both sides.
PACKAGING:	Each mattress is individually wrapped in plastic and heat sealed to protect it from dirt or damage during shipping and handling.
CERTIFICATION:	Prestige Fabricators Inc. certifies that this mattress is manufactured in compliance with CFR 1633 Standard for the Flammability of Mattresses.

Page 1