

Project:

Thin-Line LED Pendant Spec Sheet

SKU: 2816.25-4 Learn more at:


https://sonnemanlight.com/thin-line-led-pendant

Description:

A system of minimally scaled LED linear pendants, uplight/downlight wall bars, and indirect light wall bars, Thin-Line is offered in a variety of lengths, finishes, and lighting configurations. Thin-Line pendants are available in single- and double-sided configurations; the single-sided configurations can be installed as a downlight or up-light, providing direct or indirect illumination. Our Optional Mini Box Canopy is also available for the Thin-Line LED Pendant.

Type #:





Dimensions

Height: 5"
Width: 48"
Length: 0.75"
Canopy/Backplate/Base: 4.5"
Hanging Details: 6' Adjustable Cord

Size: 4' One-Sided

Canopy/Backplate/Base Height: 0.5

Electrical Specs

Bulb(s) Included?: Bulb 1 Type: Integral LED **Bulb Quantity:** Input Voltage: 120VAC Wattage: 22 Initial Lumens: 1450 **Delivered Lumens:** 900 3000K Color Temperature: CRI: 90 Power Supply Type: Driver Power Supply Quantity: Power Supply Location: Remote Dimming Type: TRIAC/ELV Bulb Max Wattage: 22

Installation

Installation:

Licensed electrician required

Sloped Ceiling Compatible?:

Minimum Hanging Height:

Maximum Hanging Height:

73.75"

Shipping

Carton 1 L x W x H: 51" X 7" X 4" Carton 1 Gross Weight: 5 LBS

Shade

Shade 1 Material: Aluminum w/Optical Acrylic

Available Finishes

Available Finishes: Bright Satin Aluminum (.16), Satin Black (.25), Satin White (.03)

General Listings

Features: Certification: Color/Finish:

Dark Sky Friendly:

Damp Rated C-ETL-US Satin Black (.25)