| Pro | ject: |  |
|-----|-------|--|
|     |       |  |

Fixture Type:

Location:

Contact:

54" Ceiling Fan

Ceiling mounted • Dry location listed



## **Description:**

This five-blade 54" ceiling fan features a white opal shade. A remote with batteries is included. This collection has a dual mount system to offer greater flexibility when installing. The 17W dimmable, 3000K LED module provides energy- and cost-savings benefits to the homeowner.

## **Specifications:**

- · Graphite (Painted)
- Steel construction DiffuserThis five-blade 54" ceiling fan features technology and style
- Includes dependable A motor for a smooth, quiet performance
- Features a 17W dimmable, 1400 Lumen, 3000K, 90CRI LED replaceable light module, offering energy- and cost-savings combined with white opal shade
- This collection has a dual mount system to offer greater flexibility when installing. The fan can be installed on a flat or sloped ceiling
- Reversible motor for year round comfort allows you to choose either a down draft (summer) or an up draft (winter)
- A hand held remote control with fan speed control and full range light dimming is included and comes with a convenient wall bracket for storage
- Remote control may be replaced by a wall control
- Rated for indoor use
- · All mounting hardware and detailed instruction are included
- Limited Lifetime Warranty on the motor for peace of mind
- Canopy covers a standard 4" octagonal recessed outlet box
- Mounting strap for outlet box included
- 80" of wire supplied





## **Dimensions:**

Diameter: 54" Height: 16"

## **Performance:**

| Number of Modules   | 1                         |
|---------------------|---------------------------|
| Input Power         | 18w                       |
| Input Voltage       | 120 V                     |
| Input Frequency     | 60 Hz                     |
| Lumens/LPW          | 1386/77 (LM-79)           |
| ССТ                 | 3000 K                    |
| CRI                 | 90 CRI                    |
| Life (hours)        | 46,000 (L70/TM-21)        |
| EMI/RFI             | Title 20                  |
| Min. Start Temp     | -10 °C                    |
| Max. Operating Temp | 40 °C                     |
| Warranty            | Limited Lifetime warranty |
| Labels              | UL Dry location listed    |