## 15" INDOOR/OUTDOOR CLEAR ICE MAKERS

Perlick<sup>®</sup>

H50IMS15" SIGNATURE SERIES MODELH50IMS-AD15" ADA COMPLIANT MODEL





Stainless Steel Door Model

Stainless Steel Door Model

### **GENERAL CLEAR ICE MAKER FEATURES**

- All models are UL-rated for outdoor use
- Available in Signature Series and ADA Compliant models
- Durable stainless steel exterior
- Front-vented forced-air refrigeration system
- Produces up to 55 lbs. of ice per 24 hour period
- Storage capacity of 22 lbs. of ice
- UL-approved for outdoor use
- Power switch accessible without panel removal

**CLEAR ICE MAKER FEATURES** 

- Easily disassembled water circuit for easy cleaning
- R-134a refrigerant

• Optional drain pump and toe kick available

1" height

- Produces a distinctive top hat shape that is clear of imperfections
- Shape also prevents ice from clumping like traditional ice makers
- Full two year warranty

7/8" dia.

Cube Dimensions

	H50IMS (Signature Series)	H50IMS-AD (ADA Compliant Series)
Overall Width	14-7/8" (37.78 cm.)	14-7/8" (37.78 cm.)
Overall Height	33-1/2" (85.09 cm.)	31-1/2" (80.01 cm.)
Overall Depth	22-9/16" (57.31 cm.)	22-9/16" (57.31 cm.)
Operating Limits	Ambient Temp Range: 45°-100°F, Water Temp Range: 45°-90°F,	
	Water Pressure: 7-113 psig, Voltage Ran	ge: 104-127V
Electrical	115V, 60Hz., 1 Phase, 3.4 amps	
Plumbing	1/2" FTP Water Inlet, 1/2" FTP Drain	
Shipping Weight	118 lbs (52.16 kg.)	

FORM NO. Z2546 REV. A-06/08/2018



# Perlick<sup>®</sup>

### SIGNATURE SERIES MODELS

H50IMS-L	Solid stainless steel door, hinged left
H50IMS-R	Solid stainless steel door, hinged right
H50IMW	Wood overlay door, hinged left or right

#### ADA COMPLIANT MODELS

H50IMS-ADL	Solid stainless steel door, hinged left
H50IMS-ADR	Solid stainless steel door, hinged right
H50IMW-AD	Wood overlay door, hinged left or right







A Water Inlet 3/4" BSP 7-1/4" (184mm) 3-118" (80mm) 5/8" (80mm) 5/8" (80mm) 5/8" (1-3/16" 2m Long Outside

ADA Compliant Series Front, Side and Back View

FORM NO. Z2546 REV. A-06/08/2018