## **Description:**

This 52" ceiling fan features an LED light source, offering both form and function with energy- and cost-savings benefits. The light kit contains a clear hammered glass shade and contains a 17W dimmable 3000K LED module. The five-blade fan features a dual mount system and has an all weather wet location rating (ABS) to accommodate a variety of settings inside and outside of the home. Available in two finish options: Antique Bronze and Forged Black.

### **Specifications:**

- · Antique Bronze (-20) (Painted)
- · Steel construction
- · Clear hammered glass Diffuser
- The light kit contains a clear hammered glass shade and contains a 17W dimmable 3000K LED module and 1400 lumens
- A wall switch is included
- The five-blade fan features a dual mount system and has an all weather wet location rat-ing (ABS blades) to accommodate a variety of settings inside and outside of the home
- Indoor ceiling fan ideal for use in great rooms, living rooms, bedrooms and bonus rooms
- Ideal for Traditional exteriors
- Reversible motor for year round comfort allows you to choose either a down draft (summer) or an up draft (winter)
- As a general rule of thumb, lighting experts suggest this fan is ideal in a room size that ranges from 226- to 400-square feet
- · Wet location listed for wet locations
- A 3/4" x 4-1/2" downrod is included. Longer accessory downrods can be ordered separately
- · Can be used to comply with Title 20.
- High Speed Energy Information: Airflow- 4585 cfm, Energy consumption- 58 watts (excluding lights), Airflow efficiency- 79 cfm/watt
- · Canopy covers a standard 4" octagonal recessed outlet box
- · Mounting strap for outlet box included
- · 80" of wire supplied
- · Walnut blades, plastic construction
- 12 degree blade pitch
- · Wall Control Included

#### Images:




#### **Dimensions:**

Diameter: 52" Height: 19-1/2"

#### Performance:

Number of Modules	1
Input Power	18w
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW	1386/77 (LM-79)
ССТ	3000 K
CRI	90 CRI
Life (hours)	50,000 (L70/TM-21)
EMI/RFI	Title 20
Min. Start Temp	-10 °C
Max. Operating Temp	40 °C
Warranty	Limited Lifetime warranty
Labels	Wet location listed



# Dimming Notes:

The following is a partial list of known compatible dimmer controls.

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.