

# Point LED Pendant

## Features

This pendant utilizes LED low voltage technology in various length metal cylinders. Cylinder is available in several color choices. Light engine includes LED module rated at 50,000 hours. Pendant is suspended from 9' adjustable cable. Product can be used over receptions desks, restaurants, and in any task lighting application. Driver is located in the canopy which mounts to standard junction box (not included).

## Construction

Pendant is supported with a 1/8" IP threaded stem and jam nut. Metal tube is made from 1/8" thick aluminum. Canopy is 5-1/2" x 1-3/8" deep and fits over a standard junction box. Canopy is retained to the junction box from the inside with 2 mounting screws and the cover is retained with a strain relief. Power supply connections must be made inside a junction box (not included).

## Finish

All exposed metal parts are satin nickel polished chrome, white or black. Canopy is painted to match finish.

## Diffuser

Diffuser is metal

## Electrical

Direct wired with a constant current low voltage electronic LED driver rated for 120 VAC. 3-Point fixture is TRIAC dimmable.

## LED

Integrated LED module capable of producing:  
3W = 240 lumens  
9W = 720 lumens  
3000K (CCT). Rated for 50,000 Hrs., 90 CRI.

## Certification

cETLus listed for damp locations.

Specifications and dimensions  
subject to change without notice.

## Ordering Information:

1-Point

\*3-Point fixture has 14", 10" and 18" high individual pendants.

LED	Source Lumens	CCT	Canopy DIA.	H	Tube DIA.
3W	240	3000K	5-1/2"	14"	7/16"

  

LED	Source Lumens	CCT	Canopy DIA.	H	Tube DIA.
9W	720	3000K	5-1/2"	18"	7/16"

