

60" Gaze Fan

Ceiling mounted • Dry location listed

Description:

Relax under a refreshing breeze created by this stylish, yet efficiently functional, Gaze ceiling fan featuring a cutting-edge LED light source. With a soft, opal white light shade, extending, distressed Ebony blades, and a Black-finish center, this ceiling fan will keep you cool as you unwind in your living room or bedroom at the end of a warm day.

- Specifications:**
- Black (-31) (painted)
 - Steel Construction
 - White Opal polycarbonate lens
 - Stylish, yet efficiently functional, oversized ceiling fan ideal for keeping you cool as you relax in a great room, living room, bedroom, or bonus room
 - Designed with a simple, Black-finish center from which extends three, 60-in, distressed Ebony or Matte Black reversible plywood blades responsible for creating a refreshing air flow
 - Effortlessly adjust the full range dimming and fan speed settings with the accompanying remote control with its batteries already included, making it ready for immediate use
 - An opal white, shatter-proof shade covers a cutting-edge LED light source that emits soft, gentle light while providing you with energy- and cost-saving benefits
 - The clean, simple design makes the fan a perfect addition to Modern or Urban Traditional settings
 - Measures 60 in X 13-1/8 in ht with 80 in lead wires and includes a 3/4 in X 6 in down rod with the ability to order longer accessory rods separately
 - Light kit includes an 18w dimmable, 3000K LED module that offers a 1400 lumens source, 90+ CRI
 - Mounting hardware included
 - Limited lifetime warranty included
 - Dimmable to 10% brightness (See Dimming Notes)canopy covers a standard 4" octagonal recessed outlet box
 - Mounting Yes for outlet box included
 - 80" of wire supplied

Images:



Dimensions:

Diameter: 60"
Length: 60"
Height: 13-1/8"

Performance:

| | |
|---------------------|--------------------------------|
| Number of Modules | 1 |
| Input Power | 18w |
| Input Voltage | 120 V |
| Input Frequency | 60 Hz |
| Lumens/LPW (Source) | 1400/77.7 (LM-82) |
| CCT | 3000 K |
| CRI | 90+ CRI |
| FCC | FCC Title 47, Part 15, Class B |
| Min. Start Temp | -10 °C |
| Max. Operating Temp | 30 °C |
| Warranty | Limited Lifetime warranty |
| Labels | UL Dry location listed |

60" Gaze Fan

Ceiling mounted • Dry location listed

Dimming Notes:

Designed to be compatible with many Triac/Forward Phase or ELV/Reverse Phase controls. The following is a partial list of known compatible dimmer controls.

Dimming Controls

| |
|--------------------------|
| Lutron - NTEVL-300 |
| Lutron - DVELV-300P |
| Lutron-DVCL-253P |
| Lutron - Caseta Wireless |
| IDevices - IDEV009 |
| Leviton – 6672 |
| Leviton – 6674 |
| Lutron - AYCL-153P |
| Lutron - TGCL-153-PH-WH |
| Lutron - AYLV-600P |
| Lutron - MAELV-601 |
| Leviton -AWSMT-EAW |
| Lutron - N-600 |

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation. Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.