



VICTORIA

Innovative ductless mini split solutions
Wall Mount Heat Pump

Up to 23 SEER 



Designed for Single Zone applications like:

Bedrooms | Living Rooms | Dining Rooms | Home Offices | Sunrooms | Basements | Computer / Server Rooms

www.cooperandhunter.us

Powered by GREE

VICTORIA

Features

- G10 Inverter Technology
- Low Ambient Cooling to 5° F (208-230Volt systems)
- Low voltage start-up
- Intelligent Defrost
- Intelligent Pre-heating
- Comfortable Sleep Mode
- Auto Swing (Vertical)
- Multiple Fan Speeds
- Auto Clean
- Dry Anti-mildew design
- LED display
- Automatic Operation
- Self-diagnosis
- Memory Function
- Timer
- Control lock
- Fan Delay function



Model		GWH09QC-A3DNA1D	GWH12QC-A3DNA1D	GWH09QC-D3DNA1D	GWH12QC-D3DNA1D	GWH18QD-D3DNA1G	GWH24QE-D3DNA1D
System Type		Heat Pump					
Power Supply		115V / 60Hz	115V / 60Hz	208-230V / 60Hz	208-230V / 60Hz	208-230V / 60Hz	208-230V / 60Hz
Rated Current Cooling	Amps	6.2	8.8	2.8	4.5	8.7	8.0
Rated Current Heating	Amps	6.2	8.8	3.5	5.5	7.5	8.4
Cooling Capacity (Min-Max)	Btu/h	9,000 (2,800-10,900)	12,000 (3,500-14,600)	9,000 (3,100-9,600)	12,000 (3,100-13,000)	18,000 (7,100-20,000)	22,000 (6,800-27,300)
Heating Capacity (Min-Max)	Btu/h	9,900 (2,100-14,000)	12,200 (2,800-16,600)	11,000 (1,900-12,000)	13,000 (2,400-14,000)	19,800 (7,300-23,500)	23,000 (6,800-30,700)
SEER/VEER		23 / 12.9	22 / 12.5	23 / 14.3	22 / 13.0	20 / 12.5	20 / 12.5
HSPF/COP		10.5 / 10.7	10.20 / 12.3	10.5 / 10.8	10.1 / 11.8	10.0 / 11.5	10.0 / 11.5
Air Flow	CFM	377/288/241/171	400/288/241/171	377/289/242/171	400/288/241/171	559/488/412/335	706/647/588/530
Sound Pressure Level - T/H/M/L	db (A)	43/38/32/26	45/40/34/28	43/39/35/29	45/39/35/29	47/43/39/35	48/44/40/36
Unit Dimension (WxHxD)	inches	33.3 x 11.1 x 8.2	33.4 x 11.1 x 8.2	33.3 x 11.1 x 8.2	33.3 x 11.1 x 8.2	38.2 x 11.8 x 8.8	42.4 x 12.8 x 9.7
Package Dimension (WxHxD)	inches	36.3 x 11.4 x 14.9	36.3 x 11.4 x 14.9	36.3 x 11.4 x 14.9	36.3 x 11.4 x 14.9	41.0 x 15.0 x 12.6	45.2 x 16.3 x 13.8
Net / Gross Weight	lb	23 / 28	23 / 28	22 / 27	22 / 27	28 / 34	34 / 42
Compressor Type		DC Inverter-driven rotary					
Sound Pressure Level	db (A)	53	53	53	54	55	59
Unit Dimension (WxHxD)	inches	33.4 x 21.3 x 12.6	33.4 x 21.3 x 12.6	33.4 x 21.3 x 12.6	33.4 x 23.6 x 12.6	38.0 x 27.6 x 15.6	38.6 x 31.1 x 16.8
Package Dimension (WxHxD)	inches	34.7 x 23.4 x 14.3	34.7 x 23.4 x 14.3	34.7 x 23.4 x 14.3	34.7 x 25.4 x 14.3	40.5 x 29.5 x 18.3	42.6 x 33.7 x 19.2
Net / Gross Weight	lb	72 / 77	77 / 84	78 / 84	86 / 93	114 / 124	142 / 153
Refrigerant / Charge	oz.	R410A / 42.3	R410A / 47.6	R410A / 45.9	R410A / 47.6	R410A / 60.0	R410A / 77.6
Line Set Size (Liquid - Suction)	inches	1/4" - 3/8"	1/4" - 1/2"	1/4" - 3/8"	1/4" - 1/2"	1/4" - 1/2"	1/4" - 5/8"
Pre-Charge	Feet	25	25	25	25	25	25
Max. Line Run	Feet	50	66	50	66	82	82
Max. Elevation	Feet	33	33	33	33	33	33
MCA	Amps	12	15	9	9	16	20
MOCP	Amps	20	25	15	15	25	30
Wire Size / # Wires		AWG12 / 4		AWG16 / 4		AWG14 / 4	AWG12 / 4
Price	USD	839	888	840	920	1495	1613



Preserving resources remains our top priority, so we've printed this piece on recycled materials.



For more information, visit | cooperandhunter.us